




ANTIKA

DESCRIPTION: Paver **TEXTURE:** Smooth

PALLET OVERVIEW*



The Antika paver is perfect as a filler in a circle, around a fan design or on a winding pathway. Antika can also be used as a mosaic frame around any design.

NOTES


See page 60 to 62 for more technical information. When used in a permeable pavement application, see page 99 to 104 for more technical information.

See page 29 for more information about applications.

JOINT WIDTH: VARIABLE
% OF SURFACE OPENING: VARIABLE
INFILTRATION RATE: 993 in./hr
 (25 227 mm/hr)

*Pallet layout may vary.

01 | Random pattern



Patterns are for design inspiration only. The installer is responsible to calculate & purchase the correct amount of material.

Specifications per pallet	Imperial	Metric
Cubing	87 ft²	8.10 m ²
Approx. Weight	2 183 lbs	990 kg
Number of rows	9	
Coverage per row	9.67 ft ²	0.90 m ²

	Unit dimensions	in	mm
A	Height	2 3/8	60
	Width	Variable	
	Length	Variable	
B	Height	2 3/8	60
	Width	Variable	
	Length	Variable	
C	Height	2 3/8	60
	Width	Variable	
	Length	Variable	
D	Height	2 3/8	60
	Width	Variable	
	Length	Variable	
E	Height	2 3/8	60
	Width	Variable	
	Length	Variable	
F	Height	2 3/8	60
	Width	Variable	
	Length	Variable	
G	Height	2 3/8	60
	Depth	Variable	
	Length	Variable	

