




# VICTORIEN 60 mm

**DESCRIPTION:** Paver **TEXTURE:** Smooth

## PALLET OVERVIEW



## NOTES


See page 60 to 62 for more technical information.

See page 29 for more information about applications.


| Specifications per pallet |                         | Imperial                                    | Metric                     |
|---------------------------|-------------------------|---------------------------------------------|----------------------------|
| 60 mm                     | Cubing                  | <b>123.70 ft<sup>2</sup></b>                | 11.50 m <sup>2</sup>       |
|                           | Approx. Weight          | 3 481 lbs                                   | 1 579 kg                   |
|                           | Number of rows          | 11                                          |                            |
|                           | Coverage per row        | 11.25 ft <sup>2</sup>                       | 1.05 m <sup>2</sup>        |
|                           | Linear coverage per row | Depth 15.87 lin. ft<br>Length 31.74 lin. ft | 4.84 lin. m<br>9.68 lin. m |

| Unit dimensions |        | in    | mm  | Units/pallet               |
|-----------------|--------|-------|-----|----------------------------|
|                 | Height | 2 3/8 | 60  | 495 units                  |
|                 | Width  | 4 1/4 | 108 | 4 units/ft <sup>2</sup>    |
|                 | Length | 8 1/2 | 216 | 43.10 units/m <sup>2</sup> |


01 | Linear pattern




02 | Linear pattern




05 | Parquet pattern



06 | Herringbone pattern



07 | Herringbone pattern



Patterns are for design inspiration only. The installer is responsible to calculate & purchase the correct amount of material.

Chocolate Brown



Shale Grey



Onyx Black






# VICTORIEN 60 mm PERMEABLE

**DESCRIPTION:** Paver **TEXTURE:** Smooth

## PALLET OVERVIEW



Permeable pavers let storm water drain away and help manage excess runoff. They also smooth the path to obtaining LEED® certification.

## NOTES

See page 99 to 104 for more technical information.


See page 29 for more information about applications.

**JOINT WIDTH:** 3/8" ( 10 mm)  
**% OF SURFACE OPENING:** 9.6 %  
**INFILTRATION RATE:** 909 in./hr  
 (23 085 mm/hr)

| Specifications per pallet |                         | Imperial          | Metric        |
|---------------------------|-------------------------|-------------------|---------------|
| 60 mm PERMEABLE           | Cubing                  | <b>110.22 ft²</b> | 10.24 m²      |
|                           | Approx. Weight          | 2 888 lbs         | 1 310 kg      |
|                           | Number of rows          | 11                |               |
|                           | Coverage per row        | 10.02 ft²         | 0.93 m²       |
|                           | Linear coverage per row | Depth             | 15.87 lin. ft |
|                           |                         | Length            | 31.74 lin. ft |
|                           |                         |                   | 4.84 lin. m   |
|                           |                         |                   | 9.68 lin. m   |




A




| Unit dimensions | in    | mm  | Units/pallet |
|-----------------|-------|-----|--------------|
| Height          | 2 3/8 | 60  | 440 units    |
| Width           | 4 1/4 | 108 |              |
| Length          | 8 1/2 | 216 |              |


01 | Linear pattern




02 | Linear pattern




03 | Linear pattern



04 | Linear pattern



05 | Parquet pattern



Patterns are for design inspiration only. The installer is responsible to calculate & purchase the correct amount of material.

Chestnut Brown

Shale Grey

